# **Honeywell**

### Genetron® 114

# 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron® 114

MSDS Number : 000000009900

Product Use Description : Aerosol propellant, Refrigerant, Carrier gas

Manufacturer or supplier's

details

Honeywell International Inc.

101 Columbia Road

Morristown, NJ 07962-1057

For more information call : 800-522-8001

+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

(24 hours/day, 7 days/week)

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : slight

#### Classification of the substance or mixture

Classification of the : Gases under pressure, Liquefied gas

substance or mixture Simple Asphyxiant

#### GHS Label elements, including precautionary statements

Page 1 / 13

# Honeywell

### Genetron® 114

# 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

Symbol(s) :

 $\Diamond$ 

Signal word : Warning

Hazard statements : Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary statements : Prevention:

Use personal protective equipment as required.

Storage:

Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise

classified

: Excessive exposure may cause central nervous system effects

including drowsiness and dizziness. Excessive exposure  $\mbox{\it may}$ 

also cause cardiac arrhythmia.

May cause frostbite.

May cause eye and skin irritation.

#### Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : CCIF2CCIF2

Chemical nature : Substance

Chemical Name CAS-No. Concentration

1,2-Dichloro-1,1,2,2-tetrafluoroethane 76-14-2 100.00 %

# Honeywell

#### Genetron® 114

### 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

#### **SECTION 4. FIRST AID MEASURES**

Inhalation : Move to fresh air. If breathing is irregular or stopped,

administer artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-

ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water.

If there is evidence of frostbite, bathe (do not rub) with

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a

physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm,

catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-

bitten areas as needed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : The product is not flammable.

**ASHRAE 34** 

Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

# Honeywell

#### Genetron® 114

#### 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

Specific hazards during

firefighting

: Contents under pressure.

This product is not flammable at ambient temperatures and

atmospheric pressure.

However, this material can ignite when mixed with air under

pressure and exposed to strong ignition sources.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

Rapid evapouration of the liquid may cause frostbite. In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2) Carbonyl halides Hydrogen fluoride Hydrogen chloride gas

Special protective equipment

for firefighters

: In the event of fire and/or explosion do not breathe fumes.

Wear self-contained breathing apparatus and protective suit.

No unprotected exposed skin areas.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Immediately evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Wear personal protective equipment. Unprotected persons

must be kept away.

Remove all sources of ignition.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

After release, disperses into the air.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is >= 19.5%.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Page 4 / 13

# Honeywell

#### Genetron® 114

### 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

The product evapourates readily.

Methods for cleaning up : Ventilate the area.

#### **SECTION 7. HANDLING AND STORAGE**

#### Handling

Handling : Handle with care.

Avoid inhalation of vapour or mist.

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Use only in well-ventilated areas.

Pressurized container. Protect from sunlight and do not expose

to temperatures exceeding 50 °C.

Follow all standard safety precautions for handling and use of

compressed gas cylinders. Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.

Always replace cap after use.

Advice on protection against fire and explosion

The product is not flammable.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

#### **Storage**

Requirements for storage areas and containers

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even

after use.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage. Store away from incompatible substances.

# Honeywell

#### Genetron® 114

### 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.

Perform filling operations only at stations with exhaust

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves

In case of contact through splashing:

Protective gloves Neoprene gloves

Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory

equipment.

Wear a positive-pressure supplied-air respirator.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

oractice

Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eves and clothing.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

**Exposure Guidelines** 

-	-xpoodio odiaoiii	.00				
	Components	CAS-No.	Value	Control	Upda	Basis
				parameters	te	

# **Honeywell**

# Genetron®114

# 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

1,2-Dichloro- 1,1,2,2- tetrafluoroethane	76-14-2	TWA: time weighted average	(1,000 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
1,2-Dichloro- 1,1,2,2- tetrafluoroethane	76-14-2	REL: Recomm ended exposure limit (REL):	7,000 mg/m3 (1,000 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
1,2-Dichloro- 1,1,2,2- tetrafluoroethane	76-14-2	PEL: Permissi ble exposure limit	7,000 mg/m3 (1,000 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
1,2-Dichloro- 1,1,2,2- tetrafluoroethane	76-14-2	TWA: time weighted average	7,000 mg/m3 (1,000 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas

Color : colourless

Odor : slight

pH : Note: neutral

Melting point/freezing point : -94 °C

Boiling point/boiling range : 4 °C

Flash point : Note: not applicable

Page 7 / 13

# Honeywell

### Genetron® 114

# 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

Evaporation rate : < 1

Method: Compared to Ether (anhydrous).

: >1

Method: Compared to CCI4.

Vapor pressure : 1.9 kPa

at 20 °C(68 °F)

Vapor density : 6 Note: (Air = 1.0)

Density : 1.5 g/cm3 at 21.1 °C

Water solubility : 0.13 g/l

Solubility in other solvents : Medium: Methanol

Note: partly soluble

Medium: Diethylether Note: partly soluble

Partition coefficient: n-

: log Pow: 2.82

octanol/water Note: The product is more soluble in octanol.

Ignition temperature : Note: not applicable

Decomposition temperature : > 260 °C

Molecular weight : 170.92 g/mol

# Honeywell

#### Genetron® 114

# 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

#### **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Conditions to avoid : Pressurized container. Protect from sunlight and do not

expose to temperatures exceeding 50 °C. Decomposes under high temperature.

Some risk may be expected of corrosive and toxic

decomposition products.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials to

avoid

: Potassium

Calcium

Powdered metals Finely divided aluminium Finely divided magnesium

Zinc

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2) Carbonyl halides Hydrogen fluoride

Hydrogen chloride gas

#### SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: > 600000 ppm

Exposure time: 2 h

Species: rat

Sensitisation : Cardiac sensitization

Species: dogs

Note: 1,2-dichloro-1,1,2,2-tetrafluoroethane (CFC-114):

Page 9 / 13

# Honeywell

#### Genetron® 114

### 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

Cardiac sensitisation threshold (dog): 45000 ppm.

Repeated dose toxicity : Species: rat

Application Route: Inhalation

NOEL: 10000 ppm Note: Subchronic toxicity

Further information : Note: May cause cardiac arrhythmia. Rapid evapouration of

the liquid may cause frostbite.

#### SECTION 12. ECOLOGICAL INFORMATION

#### Further information on ecology

Additional ecological

information

: This product contains greenhouse gases which may

contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any

residual must be recovered.

This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

Section 611 requires the following label text on all shipments

of this product:

Warning: Contains Dichlorotetrafluoroethane (CFC-114), a substance which harms public health and environment by

destroying ozone in the upper atmosphere.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

Note : This product is subject to U.S. Environmental Protection

Agency Clean Air Act Regulations Section 608 in 40 CFR Part

82 regarding refrigerant recycling.

Page 10 / 13

# Honeywell

### Genetron® 114

# 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

#### **SECTION 14. TRANSPORT INFORMATION**

**DOT** UN/ID No. : UN 1958

Proper shipping name : 1,2-Dichloro-1,1,2,2-tetrafluoroethane

Class 2.2

Packing group

Hazard Labels 2.2

IATA UN/ID No. : UN 1958

Description of the goods : 1,2-Dichloro-1,1,2,2-tetrafluoroethane

Class : 2.2 Hazard Labels : 2.2

Packing instruction (cargo : 200

aircraft)

Packing instruction : 200

(passenger aircraft)

**IMDG** UN/ID No. : UN 1958

Description of the goods : 1,2-Dichloro-1,1,2,2-tetrafluoroethane

Class : 2.2 Hazard Labels : 2.2 EmS Number : F-C, S-V

Marine pollutant : no

#### **SECTION 15. REGULATORY INFORMATION**

#### **Inventories**

US. Toxic Substances : On TSCA Inventory

Control Act

Australia. Industrial : On the inventory, or in compliance with the inventory

Chemical (Notification and

Assessment) Act

: All components of this product are on the Canadian DSL.

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)

Japan. Kashin-Hou Law : On the inventory, or in compliance with the inventory

Page 11 / 13

# Honeywell

#### Genetron® 114

## 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

List

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control

: On the inventory, or in compliance with the inventory

Act

Chemical Substances

China. Inventory of Existing: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZloC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

#### **National regulatory information**

: SARA 302: No chemicals in this material are subject to the **SARA 302 Components** 

reporting requirements of SARA Title III, Section 302.

**SARA 313 Components** : The following components are subject to reporting levels

> established by SARA Title III, Section 313: 1,2-Dichloro-1,1,2,2-76-14-2

tetrafluoroethane

SARA 311/312 Hazards : Acute Health Hazard

Sudden Release of Pressure Hazard

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : 1,2-Dichloro-1,1,2,2-76-14-2

tetrafluoroethane

Page 12 / 13

# Honeywell

#### Genetron® 114

#### 00000009900

Version 2.3 Revision Date 07/29/2014 Print Date 06/22/2015

**New Jersey RTK** : 1,2-Dichloro-1,1,2,2- 76-14-2

tetrafluoroethane

**Pennsylvania RTK** : 1,2-Dichloro-1,1,2,2- 76-14-2

tetrafluoroethane

WHMIS Classification : A: Compressed Gas

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

#### **SECTION 16. OTHER INFORMATION**

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

#### **Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 05/21/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group