



ACCORDING TO US CFR 1910.1200

**1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

## 1.1 Product identifier

Product Name	1,1,1,2-Tetrafluoroethane (R134a)
Trade Name	REFRIGERANT 134A, HFC 134A.
Synonym(s)	Tetrafluoroethane.
CAS No.	811-97-2
EC No.	212-377-0

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Refrigerant.
Uses Advised Against	Not known.

## 1.3 Details of the supplier of the safety data sheet

Company Identification	Hudson Technologies Company
Address	PO Box 1541 One Blue Hill Plaza Pearl River, New York USA
Postal code	10965
Telephone	+1 (845) 735 3905
Fax	+1 (845) 512 6070
E-mail	<a href="mailto:information@hudsontech.com">information@hudsontech.com</a>

## 1.4 Emergency telephone number

Company	+1 (800) 501 4376
CHEMTREC (U.S.)	+1 (800) 424 9300
INTERNATIONAL	+1 (703) 527 3887

**2. SECTION 2: HAZARDS IDENTIFICATION**

## 2.1 Classification of the substance or mixture

US CFR 1910.1200	Gases under pressure; Press. Gas; Liquefied gas.
------------------	--

## 2.2 Label elements

Product Name 1,1,1,2-Tetrafluoroethane (R134a)

Hazard Pictogram(s)



GHS04

Signal Word(s) Warning.

Hazard Statement(s) H280: Contains gas under pressure; may explode if heated.  
OSHA-H01: MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.  
CGA-HG01: MAY CAUSE FROSTBITE.

Precautionary Statement(s) P202: Do not handle until all safety precautions have been read and understood.  
P262: Do not get in eyes, on skin, or on clothing.  
P271+P403: Use and store only outdoors or in a well-ventilated place.  
P304, P340, P313: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.  
P302, P336, P315: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.  
P410+P403: Protect from sunlight. Store in a well-ventilated place.

## 2.3 Other hazards

May cause asphyxiation when concentrations are sufficient to reduce oxygen below safe breathing levels.

May cause frost-bite.

## 2.4 Additional Information

CGA-PG05: Use a back flow preventive device in the piping.  
CGA-PG06: Close valve after each use and when empty.  
CGA-PG02 : Protect from sunlight when ambient temperature exceeds 52 °C (125 °F).

CGA-PG27: Read and follow the Safety Data Sheet (SDS) before use.

This SDS is available in languages other than English.

**3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENT(S)	Common Names	CAS No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
1,1,1,2-Tetrafluoroethane	Tetrafluoroethane, REFRIGERANT 134A, HFC 134A.	811-97-2	100	Press. Gas, Liquefied gas; H280	GHS04

**4. SECTION 4: FIRST AID MEASURES**

4.1 Description of first aid measures

- Inhalation                                      If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, apply artificial respiration. Get medical attention.
- Skin Contact                                    Flush skin with large amounts of water. Thaw frosted parts with lukewarm water. Do no rub affected area. If symptoms persist, obtain medical attention.
- Eye Contact                                     Flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, obtain medical attention.
- Ingestion                                        Unlikely route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation: High concentrations: Headache, Dizziness, Confusion, Loss of coordination, Nausea, Unconsciousness.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## 5. SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable Extinguishing media As appropriate for surrounding fire.

Unsuitable extinguishing media None.

### 5.2 Special hazards arising from the substance or mixture

Contains gas under pressure; may explode if heated. The product should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. Decomposes in a fire giving off toxic fumes: Hydrofluoric acid, Carbonyl fluoride.

### 5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep containers cool by spraying with water if exposed to fire. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.

## 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Stop leak if safe to do so. Wear appropriate personal protective equipment, avoid direct contact.

### 6.2 Environmental precautions

Do not allow to enter drains, sewers or watercourses.

### 6.3 Methods and material for containment and cleaning up

Allow small spillages to evaporate provided there is adequate ventilation.

### 6.4 Reference to other sections

See Also Section 8, 13.

## 7. SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Provide sufficient ventilation. Avoid breathing gas. Avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye

protection/face protection. Do not drag, roll, slide or drop cylinders. Use a suitable hand truck design for cylinder movement. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object into valve cap openings. Doing so may damage valve causing a leak to occur. Secure cylinders in an upright position at all times, close all valves when not in use. Keep closed even when empty. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Protect from sunlight. Store in a well-ventilated place.

Storage temperature

<125°F (52°C)

Storage life

Stable under normal conditions.

Incompatible materials

Potassium, Calcium, Powdered Aluminium, Magnesium and Zinc.

**8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

8.1 Control parameters

Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note
1,1,1,2-Tetrafluoroethane	811-97-2	1000	4240			

Remark Workplace Environmental Exposure Level (AIHA)

8.2 Exposure controls

Appropriate engineering controls Ensure adequate ventilation.

Personal protection equipment



Eye Protection

Wear eye/face protection.



Skin protection

Wear suitable gloves.



Respiratory protection type A may be appropriate.

Where engineering controls are not fitted or inadequate wear suitable respiratory protective equipment. A suitable mask with filter

Thermal hazards

Not applicable.

## 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	Gas.
	Color: Colorless.
Color	Colorless.
Odor	Slight ethereal.
Odor threshold	Not established.
pH	Neutral.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	-15.7°F (-26.5°C)
Flash Point	Not applicable.
Evaporation rate	>1 (CC14 =1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapor pressure	96 psia @ 77°F (25°C)
Vapor density	3.6 @ 77°F (25°C) (Air = 1)
Density (g/ml)	Not available.
Relative density	1.208 @ 77°F (25°C)
Solubility(ies)	Solubility (Water): 0.15 WT% @ 77°F (25°C) Solubility (Other): Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	>1369°F (>743°C)
Decomposition Temperature (°C)	>482°F (250°C)
Viscosity	Not applicable.
Explosive properties	Not explosive.





STOT - single exposure	None anticipated.
STOT - repeated exposure	None anticipated.
Aspiration hazard	Not classified.
11.2 Other information	
	Not known.

## 12. SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates. EC50 (48 hour) (Daphnia magna) = 980mg/l
Toxicity - Fish	Low toxicity to fish. LC50 (96 hour) (Oncorhynchus mykiss) = 450mg/l
Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment	Not classified.
Compartment	
Toxicity - Terrestrial	Not classified.
Compartment	

### 12.2. Persistence and Degradation

Not readily biodegradable.

### 12.3. Bioaccumulative potential

The substance has low potential for bioaccumulation.

### 12.4. Mobility in soil

Not applicable.

### 12.5 Other adverse effects

None anticipated.

## 13. SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Containers must not be punctured or destroyed by burning, even when empty. Refer to manufacturer/supplier for information on recovery/recycling.

### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.



R-134A is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

**14. SECTION 14: TRANSPORT INFORMATION**

14.1 UN number

UN No. 3159

14.2 UN proper shipping name

UN proper shipping name 1,1,1,2-TETRAFLUOROETHANE.

14.3 Transport hazard class(es)

ADR/RID Class 2.2  
 IMDG Class 2.2  
 IMDG EMS Not available.

ICAO/IATA

Excepted Quantities E1  
 Passenger and Cargo Aircraft 75kg

Limited Quantities Packing

Instructions

Cargo Aircraft Limited Quantities 150kg

Max net Qty

Special Provisions Not applicable.

Emergency Response 126

Guidebook (ERG) Code

ADR Classification Code 2A

ADR HIN 20

ADR Transport Category 3

Tunnel Restriction Code C/E

Emergency Action Code 2TE

Advice on Additional Personal Not applicable.

Protection (APP)

14.4 Packing group

Packing group Not applicable.

Labels 2.2





Special Provisions Not applicable.  
Limited Quantities 120 m  
Excepted Quantities E1  
Mixed Packing Instructions for Packages P200  
Special Packing Provisions for Packages Not applicable.  
Mixed Packing Instructions for Packages MP9  
14.5 Environmental hazards  
Environmental hazards Not classified as a Marine Pollutant.  
14.6 Special precautions for user  
Special precautions for user Not known.

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Packing Instructions for Portable (M) T50  
Tanks  
Special Provisions for Portable Tanks Not applicable.  
Tank Code for Tanks PxBN(M)  
Special Provisions for Tanks TA4 TT9  
Vehicle for Tank Carriage AT  
Special Provisions for Carriage - Packages Not applicable.  
Special Provisions for Carriage - Bulk Not applicable.  
Special Provisions for Carriage - Loading, Unloading and Handling CV9 CV10 CV36  
Special Provisions for Carriage - Operation Not applicable.

### 15. SECTION 15: REGULATORY INFORMATION

#### 15.1 Federal

Toxic and hazardous substances (29 CFR 1910; Subpart Z ) Not listed.  
National emission standards for Not listed.



hazardous air pollutants (40 CFR  
61.01)

Title III Consolidated List of Lists Not listed.

TSCA (Toxic Substance Control Act) 1,1,1,2-Tetrafluoroethane (CAS No. 811-97-2).

CAA 602 - Ozone Depleting Substances (ODS) Not listed.

15.2 State

State Right to Know Lists Not listed.

Proposition 65 (California) Not listed.

15.3 Other

OSPAR List of Chemicals for Priority Action Not listed.

NTP (National Toxicology Program) Not listed.

OSHA (List of Highly Hazardous Chemicals, Toxics and Reactives) Not listed.

IARC (International Agency for Research on Cancer) Not listed.

**16. SECTION 16: OTHER INFORMATION**

The following sections contain 1-16 revisions or new statements:

NFPA		HMIS	
Health	1	Health	1

Fire	0	Flammability	1
Instability	1	Physical hazards	0

LEGEND:

Hazard Pictogram(s)



GHS04

Hazard Statement(s) H280: Contains gas under pressure; may explode if heated.

Precautionary Statement(s) P410+P403: Protect from sunlight. Store in a well-ventilated place.

Additional Information required by Federal Standard 313 Rev. E:

Contract or Solicitation Number: SPE4A6-16-D-0226

Prime Contractor: Hudson Technologies, Inc.

Prime Contractor CAGE: 7DSQ0

Manufacturer/Contractor CAGE: 7AHB8

National Stock Number (NSN): 6830013706207, 6830013708756, 6830013909622, 6830014126362, 6830015278354, 6830015558678

Specification Reference: A-A-58060B NOT 1

Disclaimers Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Hudson Technologies Company gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Hudson Technologies Company accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.