

ACCORDING TO US CFR 1910.1200

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name	R-402B
Synonym(s)	REFRIGERANT GAS MIX.
CAS No.	Mixture.
EC No.	Mixture.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Refrigerant.
Uses Advised Against	Not known.

1.3 Details of the supplier of the safety data sheet

Company Identification	Hudson Technologies Company
Address	PO Box 1541 One Blue Hill Plaza Pearl River, New York USA
Postal code	10965
Telephone	+1 (800) 953 2244
Fax	+1 (845) 512 6070
E-mail	information@hudsontech.com

1.4 Emergency telephone number

Company	+1 (800) 501 4376
CHEMTREC (U.S.)	+1 (800) 424 9300
INTERNATIONAL	+1 (703) 527 3887

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

US CFR 1910.1200	Gases under pressure; Press. Gas; Liquefied gas. Ozone 1; Harms public health and the environment by destroying ozone in the upper atmosphere.
------------------	---

2.2 Label elements

Product Name LIQUEFIED GAS, N.O.S. (CHLORODIFLUOROMETHANE, PENTAFLUOROETHANE) (R-402B)

Hazard Pictogram(s)



GHS04

Signal Word(s) Warning.

Hazard Statement(s) H280: Contains gas under pressure; may explode if heated.
OSHA-H01: MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Precautionary Statement(s) P202: Do not handle until all safety precautions have been read and understood.
P262: Do not get in eyes, on skin, or on clothing.
P304, P340, P313: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.
P410+P403: Protect from sunlight. Store in a well-ventilated place.
P502: Refer to manufacturer for information on recovery/recycling.

2.3 Other hazards

May cause asphyxiation when concentrations are sufficient to reduce oxygen below safe breathing levels.

May cause frost-bite.

2.4 Additional Information

CGA-PG05: Use a back flow preventive device in the piping.

CGA-PG06: Close valve after each use and when empty.

CGA-PG02 : Protect from sunlight when ambient temperature exceeds 52 °C (125 °F).

CGA-PG27: Read and follow the Safety Data Sheet (SDS) before use.

This SDS is available in languages other than English.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT(S)	CAS No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Chlorodifluoromethane (R-22)	75-45-6	60	Press. Gas, Liquefied gas; H280, Ozone. 1; H420	GHS04 GHS07
Pentafluoroethane (R-125)	354-33-6	38	Press. Gas, Liquefied gas; H280	GHS04
Propane (R-290)	74-98-6	2	Flam. Gas 1; H220, Press. Gas, Liquefied gas; H280	GHS02 GHS04

4. SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, apply artificial respiration. Get medical attention.
Skin Contact	Flush skin with large amounts of water. Thaw frosted parts with lukewarm water. Do no rub affected area. If symptoms persist, obtain medical attention.
Eye Contact	Flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, obtain medical attention.
Ingestion	Unlikely route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation: High concentrations: Headache, Dizziness, Confusion, Loss of coordination, Nausea, Unconsciousness.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to a physician: Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media As appropriate for surrounding fire.

Unsuitable extinguishing media None.

5.2 Special hazards arising from the substance or mixture

Contains gas under pressure; may explode if heated. The product should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment.

Decomposes in a fire giving off toxic fumes: Hydrofluoric acid, Hydrochloric acid, carbonyl halides, Oxides of carbon.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions. Keep containers cool by spraying with water if exposed to fire.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate area. Shut off leaks if without risk. Ensure adequate ventilation. Wear appropriate personal protective equipment, avoid direct contact.

6.2 Environmental precautions

Do not allow to enter drains, sewers or watercourses. Spills and releases may have to be reported to Federal and/or local authorities.

6.3 Methods and material for containment and cleaning up

Allow small spillages to evaporate provided there is adequate ventilation. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapours might collect.

6.4 Reference to other sections

See Also Section 8, 13.

7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Provide sufficient ventilation. Avoid breathing gas. Avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye

protection/face protection. Do not drag, roll, slide or drop cylinders. Use a suitable hand truck design for cylinder movement. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object into valve cap openings. Doing so may damage valve causing a leak to occur. Secure cylinders in an upright position at all times, close all valves when not in use. Keep closed even when empty. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Protect from sunlight. Store in a well-ventilated place.

Storage temperature

<125°F (52°C)

Storage life

Stable under normal conditions.

Incompatible materials

Strong oxidizing agents, Chlorine, Potassium, Calcium, Powdered Aluminium, Magnesium and Zinc.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Chlorodifluoromethane (R-22)	75-45-6	1000	3540			TLV (ACGIH)
Pentafluoroethane (R-125)	354-33-6	1000	4900			AIHA
Propane (R-290)	74-98-6	2500				TLV (ACGIH)
		1000	1800			PEL (OSHA)

Remark

TLV: Threshold Limit Value (ACGIH)

Workplace Environmental Exposure Level (AIHA)

OSHA = Occupational Safety and Health Administration

8.2 Exposure controls

Appropriate engineering controls Ensure adequate ventilation.

Personal protection equipment



Eye Protection

Wear eye/face protection.



Skin protection

Wear suitable gloves.



Respiratory protection type A may be appropriate.

Where engineering controls are not fitted or inadequate wear suitable respiratory protective equipment. A suitable mask with filter

Thermal hazards

Not applicable.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Gas.
	Color: Colorless.
Odor	Slight ethereal.
Odor threshold	Not established.
pH	Neutral.
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	-56.6°F (-49.2°C)
Flash Point	Not applicable.
Evaporation rate	>1 (CC14 =1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapor pressure	193.6 psia @ 77°F (25°C)
Vapor density	Not available.
Density	1.152 g/cc @ 77°F (25°C)
Relative density	Not available.
Solubility(ies)	Solubility (Water): Not determined. Solubility (Other): Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not applicable.

Decomposition Temperature (°C) Not available.

Viscosity Not applicable.

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

9.2 Other information

Percent Volatile (%) 100%

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Keep away from heat and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents, Chlorine, Potassium, Calcium, Powdered Aluminium, Magnesium and Zinc.

10.6 Hazardous decomposition product(s)

Halogens, halogen acids and possibly carbonyl halides.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion Low acute toxicity.

Acute toxicity - Skin Contact Low acute toxicity.

Acute toxicity - Inhalation Low acute toxicity.

Chlorodifluoromethane:

LC50 (6h): >150,000 ppm

Skin corrosion/irritation Non-irritant.

Serious eye damage/irritation	Non-irritant.
Skin sensitization data	Not classified.
Respiratory sensitization data	Not classified.
Germ cell mutagenicity	There is no evidence of mutagenic potential.
Carcinogenicity	No evidence of carcinogenicity.
Reproductive toxicity	Not classified.
Lactation	Not classified.
STOT - single exposure	None anticipated.
STOT - repeated exposure	None anticipated.
Aspiration hazard	Not classified.
11.2 Other information	Not known.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity - Aquatic invertebrates Low toxicity to invertebrates.
 Chlorodifluoromethane:
 EC50 (48 hour) (Daphnia magna): 433mg/l

Toxicity - Fish Low toxicity to fish.
 Chlorodifluoromethane:
 LC50 (96 hour) (Danio rerio): 777mg/l

Toxicity - Algae Low toxicity to algae.

Toxicity - Sediment Not classified.

Compartment

Toxicity - Terrestrial Not classified.

Compartment

12.2. Persistence and Degradation

Not readily biodegradable.

12.3. Bioaccumulative potential

The product has low potential for bioaccumulation.

Chlorodifluoromethane: Log Kow < 4

12.4. Mobility in soil

Not applicable.

12.5 Other adverse effects

Harms public health and the environment by destroying ozone in the upper atmosphere.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Containers must not be punctured or destroyed by burning, even when empty. Refer to manufacturer/supplier for information on recovery/recycling.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number

UN No. 3163

14.2 UN proper shipping name

UN proper shipping name LIQUEFIED GAS, N.O.S. (CHLORODIFLUOROMETHANE, PENTAFLUOROETHANE).

14.3 Transport hazard class(es)

ADR/RID Class 2.2
 IMDG Class 2.2
 IMDG EMS Not available.

ICAO/IATA

Excepted Quantities E1
 Passenger and Cargo Aircraft Forbidden for transport by air.

Limited Quantities Packing

Instructions

Passenger and Cargo Aircraft Forbidden for transport by air.

Limited Quantities Max net Qty

Special Provisions Not applicable.

Emergency Response 2L

Guidebook (ERG) Code

ADR Classification Code 2A

ADR HIN 20

ADR Transport Category 3

Tunnel Restriction Code C/E

Emergency Action Code 2TE

Advice on Additional Personal Protection (APP) Not applicable.

14.4 Packing group

Packing group Not applicable.

Labels 2.2



Special Provisions 274

Limited Quantities 120 m

Excepted Quantities E1

Mixed Packing Instructions for Packages P200

Special Packing Provisions for Packages Not applicable.

Mixed Packing Instructions for Packages MP9

14.5 Environmental hazards
 Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user
 Special precautions for user Not known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Packing Instructions for Portable (M) T50

Tanks
 Special Provisions for Portable Tanks Not applicable.

Tanks
 Tank Code for Tanks PxBN(M)

Special Provisions for Tanks TA4 TT9

Vehicle for Tank Carriage AT
 Special Provisions for Carriage - Not applicable.

Packages
 Special Provisions for Carriage - Not applicable.

Bulk
 Special Provisions for Carriage - CV9 CV10 CV36

Loading, Unloading and Handling



Special Provisions for Carriage - Not applicable.

Operation

15. SECTION 15: REGULATORY INFORMATION

15.1 Federal

Toxic and hazardous substances All chemicals are not listed.

(29 CFR 1910; Subpart Z)

National emission standards for All chemicals are not listed.

hazardous air pollutants (40 CFR

61.01)

Title III Consolidated List of Lists Chlorodifluoromethane (CAS No. 75-45-6),

Propane (CAS No. 74-98-6).

TSCA (Toxic Substance Control All chemicals listed.

Act)

SARA 313 Toxic Chemicals Chlorodifluoromethane (CAS No. 75-45-6).

CAA 602 - Ozone Depleting Chlorodifluoromethane (CAS No. 75-45-6) – Class II ODS.

Substances (ODS)

15.2 State

State Right to Know Lists Chlorodifluoromethane (CAS No. 75-45-6)

Listed in: New Jersey, Pennsylvania, Rhode Island, Minnesota

Propane (CAS No. 74-98-6)

Listed in: New Jersey, Pennsylvania, Minnesota

Proposition 65 (California) All chemicals are not listed.

15.3 Other

OSPAR List of Chemicals for All chemicals are not listed.

Priority Action

NTP (National Toxicology All chemicals are not listed.

Program)

OSHA All chemicals are not listed.

(List of Highly Hazardous
Chemicals, Toxics and
Reactives)

IARC (International Agency for
Research on Cancer) Chlorodifluoromethane (CAS No. 75-45-6).

16. SECTION 16: OTHER INFORMATION

The following sections contain 1-16
revisions or new statements:

NFPA		HMIS	
Health	2	Health	1
Fire	1	Flammability	0
Instability	0	Physical hazards	1

LEGEND:

Hazard Pictogram(s)



GHS04

Hazard Statement(s)

H280: Contains gas under pressure; may explode if heated.

H420: Harms public health and the environment by destroying ozone in the upper atmosphere.

Precautionary Statement(s)

P410+P403: Protect from sunlight. Store in a well-ventilated place.

P502: Refer to manufacturer for information on recovery/recycling.

Additional Information required by Federal Standard 313 Rev. E:



SAFETY DATA SHEET

04-Apr-2017

Contract or Solicitation Number: SPE4A6-16-D-0226
Prime Contractor: Hudson Technologies, Inc.
Prime Contractor CAGE: 7DSQ0

National Stock Number (NSN): 6830013920991
Specification Reference:

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Hudson Technologies Company gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Hudson Technologies Company accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.