

November 21, 2018 Revised

SAFETY DATA SHEET R-22

1. IDENTIFICATION

PRODUCT NAME: Refrigerant 22

SYNONYMS: R-22, REFRIGERANT 22, HCFC 22, AmeriPure® R22, Chlorodifluoromethane, Monochlorodifluoromethane

RECOMMENDED USE: Refrigerant

DISTRIBUTOR: Hudson Technologies Company
ADDRESS: 300 Tice Blvd., Suite 290
Woodcliff Lake, NJ 07677


EMERGENCY PHONE: 1- 800-501-4376
CHEMTREC PHONE: 1-800-424-9300
INFORMATION PHONE: 1-800-953-2244

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Colorless, volatile liquid with ethereal and faint sweetish odor. Non-flammable material. Contact with the liquid may cause frostbite. Overexposure to vapors by inhalation may cause dizziness and loss of concentration. At higher levels, central nervous system depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250°C), decomposition products may include Hydrochloric Acid (HCL), Hydrofluoric Acid (HF) and carbonyl halides.

HAZARD

CLASSIFICATION: Gases Under Pressure
USDOT Hazard Class 2.2, Non-Flammable Gas



SIGNAL WORD: WARNING

HAZARD

STATEMENTS: Gas under pressure; may explode if heated
Harms public health and the environment by destroying ozone in the upper atmosphere
Harmful in contact with skin - may cause frostbite
May displace oxygen and cause rapid suffocation. Inhalation of high concentrations of vapor is harmful and may cause heart irregularities, unconsciousness, or death.

November 21, 2018 Revised

SAFETY DATA SHEET R-22

PRECAUTIONARY STATEMENTS

PREVENTION: Do not breathe vapors. Use only with adequate ventilation - never in a closed space. Wear protective gloves. Wear eye protection.

RESPONSE: If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a physician. If not breathing, give artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen. Avoid stimulants. Do not give adrenalin. If on skin: Wash with plenty of water (not hot water) or use other means to warm skin slowly. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician.

STORAGE: Protect from sunlight. Store in well-ventilated place. Do not heat above 120°F (50°C). Do not store in damp areas.

DISPOSAL: Comply with Federal, State and local regulations. Reclaim by distillation or remove to a permitted waste disposal facility

CARCINOGENICITY: IARC-3/TLV-A4 – Not classifiable as a human carcinogen due to a lack of data.

OSHA: <0.1%

ACGIH: <0.1%

NTP: <0.1%

IARC: <0.1%

3. COMPOSITION / INFORMATION ON INGREDIENTS

PRODUCT NAME: Refrigerant 22

SYNONYMS: R-22, REFRIGERANT 22, HCFC 22, AmeriPure® R22, Chlorodifluoromethane, Monochlorodifluoromethane

INGREDIENT NAME CAS NUMBER WEIGHT %

<u>Ingredient Name</u>	<u>CAS Number</u>
Chlorodifluoromethane (HCFC-22)	75-45-6

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of this Safety Data Sheet.

4. FIRST AID MEASURES

SKIN: Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

SAFETY DATA SHEET R-22**7. HANDLING AND STORAGE**

NORMAL HANDLING: Always wear recommended personal protective equipment.

Avoid breathing vapors and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders only. Follow standard safety precautions for handling and use of compressed gas cylinders. R-22 should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

STORAGE RECOMMENDATIONS:

Store in a cool, well-ventilated area of low fire risk and keep out of direct sunlight. Protect cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty. Cylinder temperatures should not exceed 52° C (125° F).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operating and storage areas.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION: Skin contact with refrigerant may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with the liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

EYE PROTECTION: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

RESPIRATORY PROTECTION: None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL of 1,000 ppm, use a self-contained, NIOSH- approved breathing apparatus or supplied air respirator. For escape: use the former or a NIOSH-approved gas mask with organic vapor canister.

ADDITIONAL RECOMMENDATIONS: Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High dose-level warning signs are recommended for areas of principle exposure. Provide eyewash stations and quick-drench shower facilities at convenient locations. For tank cleaning operations, see OSHA regulations, 29 CFR 1910.132 and 29 CFR 1910.133.

EXPOSURE GUIDELINES

<u>INGREDIENT NAME</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER LIMIT</u>
Chlorodifluoromethane	None	None	*1000 ppm TWA (8hr); *3,540 mg/m ³

* = Workplace Environmental Exposure Level (AIHA and NIOSH)

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

Hydrogen Fluoride: ACGIH TLV: 3 ppm ceiling

November 21, 2018 Revised

SAFETY DATA SHEET R-22

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear, colorless liquefied gas
ODOR:	Slight ethereal
PHYSICAL STATE:	liquefied gas
PH	Neutral
BOILING POINT (@ 736 mm Hg):	F: -41.4 C: -40.8
VAPOR PRESSURE (psia):	151 @ 77F (25C)
VAPOR DENSITY (AIR = 1):	3.03 @ 77F (25C)
SPECIFIC GRAVITY (H ₂ O = 1):	1.3 @ 77F (25C)
EVAPORATION RATE (CCL ₄ =1):	N/R
SOLUBILITY IN WATER (@14.7 psia):	0.3 WT% @ 77F (25C)
PERCENT SOLIDS BY WEIGHT:	Gas
PERCENT VOLATILE:	100% By Wt
VOLATILE ORGANIC COMPOUNDS (VOC):	Gas

10. STABILITY AND REACTIVITY

NORMALLY STABLE (CONDITIONS TO AVOID):

The product is stable.

Do not mix with oxygen or air above atmospheric pressure. Any source of high temperature, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

INCOMPATIBILITIES:

Under specific conditions: e.g. very high temperatures and/or appropriate pressures – Freshly abraded aluminum surfaces may cause strong exothermic reaction. Chemically active metals: potassium, calcium, powdered aluminum, magnesium and zinc.

HAZARDOUS DECOMPOSITION PRODUCTS:

Halogens, halogen acids and possibly carbonyl halides. These materials are toxic and irritating.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

Animal Data: Inhalation 4 hour LC 50: 220,000 ppm in rats; Oral ALD : >1,000 mg/kg in rats

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

48-hour EC50, Daphnia magna: 433 mg/L

Degradability (BOD): R-22 is a gas at room temperature; therefore, it is unlikely to remain in water.

Octanol Water Partition Coefficient: 1.08

November 21, 2018 Revised

SAFETY DATA SHEET R-22

13. DISPOSAL CONSIDERATIONS

RCRA - Not a hazardous waste.

OTHER DISPOSAL CONSIDERATIONS:

Disposal must comply with federal, state, and local disposal or discharge laws. R-22 is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

HAZARD CLASS:	2.2
PROPER SHIPPING NAME:	CHLORODIFLUOROMETHANE
ID NUMBER:	UN1018
PACKING GROUP:	N/A
LABEL STATEMENT:	NONFLAMMABLE GAS
SHIPPING CONTAINERS:	Tank Cars, cylinders, ton tanks

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

15. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: Components listed on the TSCA inventory

OTHER TSCA ISSUES: None

SARA TITLE III / CERCLA

“Reportable Quantities” (RQs) and/or “Threshold Planning Quantities” (TPQs) exist for the following ingredients.

<u>INGREDIENT NAME</u>	<u>SARA / CERCLA RQ (lb.)</u>	<u>SARA EHS TPQ (lb.)</u>
No ingredients listed in this section		

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: IMMEDIATE PRESSURE

SARA 313 TOXIC CHEMICALS: R22 is listed as a SARA 313 “Toxic Chemical”. CAS numbers and weight percents are found in Section 3.

STATE RIGHT-TO-KNOW : R22 is a listed chemical for state right-to-know purposes.

November 21, 2018 Revised

SAFETY DATA SHEET R-22

ADDITIONAL REGULATORY INFORMATION: R-22 is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

WARNING:

Do not vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

Chlorodifluoromethane (HCFC-22), is a substance that harms public health and environment by destroying ozone in the upper atmosphere. Chlorodifluoromethane is a greenhouse gas which may contribute to global warming.

California Prop. 65: This product does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

DISCLAIMER: The above information is based upon technical information believed to be accurate but does not purport to all-inclusive and should be used only as a guide. Hudson Technologies Company shall not be held liable for any damage from handling or from contact with this product. No warranty of merchantability or any warranty, express or implied is made with respect to such information