

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2017
3.0	13.10.2017	1354839-00031	Date of first issue: 27.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	Opteon™ XL40 (R-454A) Refrigerant
Product code	:	D15438149
SDS-Identcode	:	130000143546

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Refrigerant
Recommended restrictions on use	:	For professional and industrial installation and use only.

1.3 Details of the supplier of the safety data sheet

Company	:	Chemours Netherlands B.V. Baanhoekweg 22 3313 LA Dordrecht Netherlands
Telephone	:	+31-(0)-78-630-1011
Telefax	:	+31-78-6163737
E-mail address of person responsible for the SDS	:	sds-support@chemours.com

1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1	H220: Extremely flammable gas.
Gases under pressure, Liquefied gas	H280: Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Response: P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 In case of leakage, eliminate all ignition sources. Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Additional Labelling

Contains fluorinated greenhouse gases. (HFC-32)

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).
May displace oxygen and cause rapid suffocation.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.
Rapid evaporation of the product may cause frostbite.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,3,3,3-Tetrafluoropropene*	754-12-1 468-710-7 01-0000019665-61-0001	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	65
Difluoromethane*	75-10-5	Flam. Gas 1; H220	35

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

	200-839-4 01-2119471312-47	Press. Gas Liquefied gas; H280	
--	-------------------------------	-----------------------------------	--

* Voluntarily-disclosed non-hazardous substance
For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
Protection of first-aiders	: No special precautions are necessary for first aid responders.
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Thaw frosted parts with lukewarm water. Do not rub affected area. Get medical attention immediately.
In case of eye contact	: Get medical attention immediately.
If swallowed	: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: May cause cardiac arrhythmia. Other symptoms potentially related to misuse or inhalation abuse are Cardiac sensitisation Anaesthetic effects Light-headedness Dizziness confusion Lack of coordination Drowsiness Unconsciousness
Risks	: Contact with liquid or refrigerated gas can cause cold burns and frostbite.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically and supportively.
-----------	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Vapours may form flammable mixture with air
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Hydrogen fluoride
Fluorine compounds
Carbon oxides
carbonyl fluoride

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fight fire remotely due to the risk of explosion.
Use water spray to cool unopened containers.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Evacuate personnel to safe areas.
Only trained personnel should re-enter the area.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

- Environmental precautions : Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

|| Retain and dispose of contaminated wash water.

6.3 Methods and material for containment and cleaning up

|| Methods for cleaning up : Ventilate the area.
Non-sparking tools should be used.
Suppress (knock down) gases/vapours/mists with a water spray jet.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

|| See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

|| Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.

|| Local/Total ventilation : Use with local exhaust ventilation.
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

|| Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Wear cold insulating gloves/ face shield/ eye protection.
Prevent backflow into the gas tank.
Open the valves slowly to prevent pressure surges.
Close valve after each use and when empty. Do NOT change or force fit connections.
Prevent the intrusion of water into the gas tank.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Avoid breathing gas.
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2017
3.0	13.10.2017	1354839-00031	Date of first issue: 27.02.2017

Hygiene measures : Never attempt to lift cylinder by its cap.
Do not drag, slide or roll cylinders.
Use a suitable hand truck for cylinder movement.
: Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable liquids
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Acutely toxic substances and mixtures
Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage temperature : < 52 °C

Further information on storage stability : The product has an indefinite shelf life when stored properly.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,3,3,3-Tetrafluoropropene	Workers	Inhalation	Long-term systemic effects	950 mg/m ³
Difluoromethane	Workers	Inhalation	Long-term systemic effects	7035 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	750 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,3,3,3-Tetrafluoropropene	Fresh water	0.1 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	1.77 mg/kg dry weight (d.w.)
	Soil	1.54 mg/kg dry weight (d.w.)
Difluoromethane	Marine water	0.01 mg/l
	Marine sediment	0.178 mg/kg dry weight (d.w.)
	Fresh water	0.142 mg/l
Difluoromethane	Intermittent use/release	1.42 mg/l
	Fresh water sediment	0.534 mg/kg

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential
Use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
Face-shield

Hand protection
Material : Low temperature resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Skin and body protection	:	Wear the following personal protective equipment: Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Organic gas and low boiling vapour type (AX)
Protective measures	:	Wear cold insulating gloves/ face shield/ eye protection.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	Liquefied gas
Colour	:	clear, colourless
Odour	:	slight, ether-like
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-48.3 °C
Flash point	:	Not applicable
Evaporation rate	:	> 1 (CCL4=1.0)
Flammability (solid, gas)	:	Flammable
Upper explosion limit / Upper flammability limit	:	Upper flammability limit < 15 %(V) Method: ASTM E681
Lower explosion limit / Lower flammability limit	:	Lower flammability limit > 8 %(V) Method: ASTM E681
Vapour pressure	:	15,244 hPa (25 °C)
Relative vapour density	:	2.83 (Air = 1.0)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Relative density	: 0.98 (25 °C)
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form flammable mixture with air
Can react with strong oxidizing agents.
Extremely flammable gas.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

|| exposure Skin contact
|| Eye contact

Acute toxicity

|| Not classified based on available information.

Components:

|| 2,3,3,3-Tetrafluoropropene:

|| Acute inhalation toxicity : LC50 (Rat): > 405000 ppm
|| Exposure time: 4 h
|| Test atmosphere: gas
||
|| Lowest observed adverse effect concentration (Dog): >
|| 120000 ppm
|| Test atmosphere: gas
|| Symptoms: Cardiac sensitisation
||
|| No observed adverse effect concentration (Dog): 120000 ppm
|| Test atmosphere: gas
|| Symptoms: Cardiac sensitisation
||
|| Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m3
|| Test atmosphere: gas
|| Symptoms: Cardiac sensitisation

|| Difluoromethane:

|| Acute inhalation toxicity : LC50 (Rat): > 520000 ppm
|| Exposure time: 4 h
|| Test atmosphere: gas
||
|| Lowest observed adverse effect concentration (Dog): >
|| 350000 ppm
|| Symptoms: Cardiac sensitisation
||
|| No observed adverse effect concentration (Dog): 350000 ppm
|| Symptoms: Cardiac sensitisation
||
|| Cardiac sensitisation threshold limit (Dog): > 735,000 mg/m3
|| Symptoms: Cardiac sensitisation

Skin corrosion/irritation

|| Not classified based on available information.

Components:

|| 2,3,3,3-Tetrafluoropropene:

|| Species: Not tested on animals
|| Result: No skin irritation

|| Difluoromethane:

|| Species: Not tested on animals

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Species: Not tested on animals

Result: No eye irritation

Difluoromethane:

Species: Not tested on animals

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Exposure routes: Skin contact

Species: Not tested on animals

Result: negative

Difluoromethane:

Exposure routes: Skin contact

Species: Not tested on animals

Result: negative

Species: Not tested on animals

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Difluoromethane:

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Carcinogenicity

|| Not classified based on available information.

Components:

|| 2,3,3,3-Tetrafluoropropene:

|| Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

|| Not classified based on available information.

Components:

|| 2,3,3,3-Tetrafluoropropene:

|| Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

|| Difluoromethane:

|| Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials

STOT - single exposure

|| Not classified based on available information.

STOT - repeated exposure

|| Not classified based on available information.

Components:

|| 2,3,3,3-Tetrafluoropropene:

|| Assessment: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

|| Difluoromethane:

|| Assessment: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity

Components:

|| 2,3,3,3-Tetrafluoropropene:

|| Species: Rat
|| NOAEL: 50000 ppm
|| LOAEL: >50000 ppm
|| Application Route: inhalation (gas)
|| Exposure time: 90 d
|| Method: OECD Test Guideline 413
|| Remarks: No significant adverse effects were reported

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Difluoromethane:

Species: Rat
NOAEL: 49100 ppm
Application Route: inhalation (gas)
Exposure time: 90 d
Remarks: No significant adverse effects were reported

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,3,3,3-Tetrafluoropropene:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 197 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae : NOEC (algae): > 100 mg/l
Exposure time: 72 h

Difluoromethane:

Toxicity to fish : LC50 (Fish): 1,507 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 652 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (algae): 142 mg/l
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC: 65.8 mg/l
Exposure time: 30 d
Species: Fish

12.2 Persistence and degradability

Components:

2,3,3,3-Tetrafluoropropene:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301F

Difluoromethane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

2,3,3,3-Tetrafluoropropene:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Difluoromethane:

Partition coefficient: n-octanol/water : log Pow: 0.714

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB)..

12.6 Other adverse effects

Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

Product:

100-year global warming potential: 238.85

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 3161
ADR	:	UN 3161
RID	:	UN 3161
IMDG	:	UN 3161
IATA (Cargo)	:	UN 3161
IATA (Passenger)	:	UN 3161 Not permitted for transport

14.2 UN proper shipping name

ADN	:	LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoropropene, Difluoromethane)
ADR	:	LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoropropene, Difluoromethane)
RID	:	LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoropropene, Difluoromethane)
IMDG	:	LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoropropene, Difluoromethane)
IATA (Cargo)	:	Liquefied gas, flammable, n.o.s. (2,3,3,3-Tetrafluoropropene, Difluoromethane)
IATA (Passenger)	:	LIQUEFIED GAS, FLAMMABLE, N.O.S. Not permitted for transport

14.3 Transport hazard class(es)

ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
IATA (Cargo)	:	2.1
IATA (Passenger)	:	Not permitted for transport

14.4 Packing group

ADN	:	
Packing group	:	Not assigned by regulation
Classification Code	:	2F
Hazard Identification Number	:	23
Labels	:	2.1
ADR	:	
Packing group	:	Not assigned by regulation
Classification Code	:	2F
Hazard Identification Number	:	23

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version 3.0 Revision Date: 13.10.2017 SDS Number: 1354839-00031 Date of last issue: 28.02.2017
Date of first issue: 27.02.2017

Labels : 2.1
Tunnel restriction code : (B/D)

RID

Packing group : Not assigned by regulation
Classification Code : 2F
Hazard Identification Number : 23
Labels : 2.1 ((13))

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 200
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2017
3.0	13.10.2017	1354839-00031	Date of first issue: 27.02.2017

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P2	FLAMMABLE GASES	Quantity 1 10 t	Quantity 2 50 t
----	-----------------	--------------------	--------------------

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

SECTION 16: Other information

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

Full text of H-Statements

H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.

Full text of other abbreviations

Flam. Gas : Flammable gases
Press. Gas : Gases under pressure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 28.02.2017
3.0	13.10.2017	1354839-00031	Date of first issue: 27.02.2017

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Flam. Gas 1	H220
Press. Gas Liquefied gas	H280

Classification procedure:

Based on product data or assessment
Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN