

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

SECTION 1. IDENTIFICATION

Product name : Opteon™ XL41 (R-454B) Refrigerant
Product code : D15443612
SDS-Identcode : 130000143545

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC
Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use


Recommended use : Refrigerant
Restrictions on use : For professional and industrial installation and use only., Do not use product for anything outside of the above specified uses

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable gases : Category 1
Gases under pressure : Liquefied gas
Simple Asphyxiant

GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Precautionary Statements : **Prevention:**
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.

Response:
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 Eliminate all ignition sources if safe to do so.

Storage:
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Other hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.
Rapid evaporation of the product may cause frostbite.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Difluoromethane#	75-10-5	68.9
2,3,3,3-Tetrafluoropropene#	754-12-1	31.1

Voluntarily-disclosed substance

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.

In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area.
Get medical attention immediately.

In case of eye contact : Get medical attention immediately.

If swallowed : Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed : May cause cardiac arrhythmia.
Other symptoms potentially related to misuse or inhalation abuse are

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Cardiac sensitization
Anaesthetic effects
Light-headedness
Dizziness
confusion
Lack of coordination
Drowsiness
Unconsciousness
Gas reduces oxygen available for breathing.
Contact with liquid or refrigerated gas can cause cold burns and frostbite.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Vapors may form flammable mixture with air
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
Carbon oxides
Fluorine compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fight fire remotely due to the risk of explosion.
Use water spray to cool unopened containers.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Only trained personnel should re-enter the area.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
- Methods and materials for containment and cleaning up : Ventilate the area.
Non-sparking tools should be used.
Suppress (knock down) gases/vapors/mists with a water spray jet.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Avoid breathing gas.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Wear cold insulating gloves/ face shield/ eye protection.
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.
Prevent backflow into the gas tank.
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.
Close valve after each use and when empty. Do NOT change or force fit connections.
Prevent the intrusion of water into the gas tank.
Never attempt to lift cylinder by its cap.
Do not drag, slide or roll cylinders.

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Use a suitable hand truck for cylinder movement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.
Separate full containers from empty containers.
Do not store near combustible materials.
Avoid area where salt or other corrosive materials are present.
Keep in properly labeled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Keep away from direct sunlight.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable liquids
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Very acutely toxic substances and mixtures
Acutely toxic substances and mixtures
Substances and mixtures with chronic toxicity

Recommended storage temperature : < 126 °F / < 52 °C

Storage period : > 10 y

Further information on storage stability : The product has an indefinite shelf life when stored properly.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Difluoromethane	75-10-5	TWA	1,000 ppm	US WEEL
2,3,3,3-Tetrafluoropropene	754-12-1	TWA	500 ppm	US WEEL

Engineering measures : Minimize workplace exposure concentrations.

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
Face-shield

Skin and body protection : Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquefied gas

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Color : colorless

Odor : slight, ether-like

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : -59.6 °F / -50.9 °C

Flash point : Not applicable

Evaporation rate : > 1
(CCL4=1.0)

Flammability (solid, gas) : Flammable

Upper explosion limit / Upper flammability limit : Upper flammability limit
23.6 %(V)
Method: ASTM E681

Lower explosion limit / Lower flammability limit : Lower flammability limit
11.3 %(V)
Method: ASTM E681

Vapor pressure : 15,856 hPa (77 °F / 25 °C)

Relative vapor density : 2.2
(Air = 1.0)

Relative density : 0.98 (77 °F / 25 °C)

Density : 0.98 g/cm³ (77 °F / 25 °C)
(as liquid)

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 925 °F / 496 °C

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : Not applicable

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Possibility of hazardous reactions : Vapors may form flammable mixture with air
Can react with strong oxidizing agents.
Flammable gas.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.
Incompatible with acids and bases.
Incompatible with oxidizing agents.
Oxygen
Peroxides
peroxide compounds
Powdered metals

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Difluoromethane:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 520000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 350000 ppm

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Test atmosphere: gas
Remarks: Cardiac sensitization

Lowest observed adverse effect concentration (Dog): > 350000 ppm
Test atmosphere: gas
Remarks: Cardiac sensitization

Cardiac sensitisation threshold limit (Dog): > 735,000 mg/m³
Test atmosphere: gas
Remarks: Cardiac sensitization

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

2,3,3,3-Tetrafluoropropene:

Acute inhalation toxicity : LC50 (Rat): > 405800 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 120000 ppm
Test atmosphere: gas
Remarks: Cardiac sensitization

Lowest observed adverse effect concentration (Dog): > 120000 ppm
Test atmosphere: gas
Remarks: Cardiac sensitization

Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m³
Test atmosphere: gas
Remarks: Cardiac sensitization

Skin corrosion/irritation

Not classified based on available information.

Components:

Difluoromethane:

Result : No skin irritation

2,3,3,3-Tetrafluoropropene:

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Difluoromethane:

Result : No eye irritation

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

2,3,3,3-Tetrafluoropropene:

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Difluoromethane:

Routes of exposure : Skin contact
Result : negative

2,3,3,3-Tetrafluoropropene:

Routes of exposure : Skin contact
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Difluoromethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

2,3,3,3-Tetrafluoropropene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: positive

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 489
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Difluoromethane:

Effects on fertility : Species: Mouse
Application Route: Inhalation
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 414
Result: negative

Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rabbit
Application Route: inhalation (gas)
Method: OECD Test Guideline 414
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

2,3,3,3-Tetrafluoropropene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 414
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, No effects on or via lactation

STOT-single exposure

Not classified based on available information.

Components:

Difluoromethane:

Routes of exposure : inhalation (gas)
Assessment : No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

2,3,3,3-Tetrafluoropropene:

Routes of exposure : inhalation (gas)
Assessment : No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Components:

Difluoromethane:

Routes of exposure : inhalation (gas)
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

2,3,3,3-Tetrafluoropropene:

Routes of exposure : inhalation (gas)
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity

Components:

Difluoromethane:

Species : Rat, male and female
NOAEL : 49100 ppm
LOAEL : > 49100 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks
Method : OECD Test Guideline 413

2,3,3,3-Tetrafluoropropene:

Species : Rat, male and female
NOAEL : 50000 ppm
LOAEL : >50000 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks
Method : OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

Components:

Difluoromethane:

No aspiration toxicity classification

2,3,3,3-Tetrafluoropropene:

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Difluoromethane:

Toxicity to fish : LC50 (Fish): 1,507 mg/l

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Exposure time: 96 h
Method: ECOSAR (Ecological Structure Activity Relationships)

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 652 mg/l
Exposure time: 48 h
Method: ECOSAR (Ecological Structure Activity Relationships)

Toxicity to algae/aquatic plants : EC50 (green algae): 142 mg/l
Exposure time: 96 h
Method: ECOSAR (Ecological Structure Activity Relationships)

2,3,3,3-Tetrafluoropropene:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 197 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): > 75 mg/l
Exposure time: 3 d
Method: OECD Test Guideline 201

Persistence and degradability

Components:

Difluoromethane:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301D

2,3,3,3-Tetrafluoropropene:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301F

Bioaccumulative potential

Components:

Difluoromethane:

Partition coefficient: n-octanol/water : log Pow: 0.714

2,3,3,3-Tetrafluoropropene:

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2 (77 °F / 25 °C)

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty pressure vessels should be returned to the supplier. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3161
Proper shipping name : LIQUEFIED GAS, FLAMMABLE, N.O.S.
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 3161
Proper shipping name : Liquefied gas, flammable, n.o.s.
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 200
Packing instruction (passenger aircraft) : Not permitted for transport

IMDG-Code

UN number : UN 3161
Proper shipping name : LIQUEFIED GAS, FLAMMABLE, N.O.S.
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)
Class : 2.1

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3161
Proper shipping name : Liquefied gas, flammable, n.o.s.
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)
Class : 2.1
Packing group : Not assigned by regulation
Labels : FLAMMABLE GAS
ERG Code : 115
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Gases under pressure
Flammable (gases, aerosols, liquids, or solids)
Simple Asphyxiant

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Difluoromethane 75-10-5
2,3,3,3-Tetrafluoropropene 754-12-1

California List of Hazardous Substances

Difluoromethane 75-10-5

International Regulations

Montreal Protocol : Difluoromethane

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version 3.18 Revision Date: 03/29/2023 SDS Number: 2732975-00021 Date of last issue: 01/13/2023
Date of first issue: 04/24/2018


Additional regulatory information

2,3,3,3-Tetrafluoropropene 754-12-1
The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.
See 40 CFR § 721.10182
This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		4
PHYSICAL HAZARD		3

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -

SAFETY DATA SHEET



Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 01/13/2023
3.18	03/29/2023	2732975-00021	Date of first issue: 04/24/2018

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8