

**DuPont™ Suva® MP39 Refrigerant**

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	DuPont™ Suva® MP39 Refrigerant
Product Grade/Type	:	ASHRAE Refrigerant number designation: R-401A
<hr/>		
Product Use	:	Refrigerant, For professional users only.
Restrictions on use	:	Do not use product for anything outside of the above specified uses
Manufacturer/Supplier	:	DuPont 1007 Market Street Wilmington, DE 19898 United States of America
Product Information	:	+1-800-441-7515 (outside the U.S. +1-302-774-1000)
Medical Emergency	:	1-800-441-3637 (outside the U.S. 1-302-774-1139)
Transport Emergency	:	CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION**Product hazard category**

Gases under pressure

Liquefied gas

Label content

Pictogram

:



**DuPont™ Suva® MP39 Refrigerant**

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

Signal word : Warning

Hazardous warnings : Contains gas under pressure; may explode if heated.

Hazardous prevention measures : Protect from sunlight. Store in a well-ventilated place.

Other hazards

Misuse or intentional inhalation abuse may lead to death without warning.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Rapid evaporation of the liquid may cause frostbite.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Chlorodifluoromethane (HCFC-22)	75-45-6	53 %
1-Chloro-1,2,2,2-tetrafluoroethane (HCFC-124)	2837-89-0	34 %
1,1-Difluoroethane (HFC-152a)	75-37-6	13 %

SECTION 4. FIRST AID MEASURES

General advice : Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.

Inhalation : Remove from exposure, lie down. Move to fresh air. Keep patient warm and at rest. Artificial respiration and/or oxygen may be necessary. Consult a physician.

**DuPont™ Suva® MP39 Refrigerant**

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

- Skin contact : Take off contaminated clothing and shoes immediately. Flush area with lukewarm water. Do not use hot water. If frostbite has occurred, call a physician.
- Eye contact : Rinse immediately with plenty of water and seek medical advice.
- Ingestion : Is not considered a potential route of exposure.
- Most important symptoms/effects, acute and delayed : Anaesthetic effects Light-headedness irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension, feeling of fainting, dizziness or weakness
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : No applicable data available.



DuPont™ Suva® MP39 Refrigerant

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

- Specific hazards** : Cylinders are equipped with pressure and temperature relief devices, but may still rupture under fire conditions. Decomposition may occur. Contact of welding or soldering torch flame with high concentrations of refrigerant can result in visible changes in the size and colour of the torch flame. This flame effect will only occur in concentrations of product well above the recommended exposure limit. Therefore stop all work and ventilate to disperse refrigerant vapors from the work area before using any open flames. This substance is not flammable in air at temperatures up to 100 deg. C (212 deg. F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other purposes. Experimental data have also been reported which indicate combustibility of this substance in the presence of certain concentrations of chlorine.
- Special protective equipment for firefighters** : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Wear neoprene gloves during cleaning up work after a fire.
- Further information** : Cool containers/tanks with water spray. Self-contained breathing apparatus (SCBA) is required if containers rupture and contents are released under fire conditions.
Water runoff should be contained and neutralized prior to release.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

- Safeguards (Personnel)** : Evacuate personnel to safe areas. Ventilate area, especially low or enclosed places where heavy vapours might collect.

**DuPont™ Suva® MP39 Refrigerant**

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

- Environmental precautions : Should not be released into the environment. In accordance with local and national regulations.
- Spill Cleanup : Evaporates. Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect.
- Accidental Release Measures : Avoid open flames and high temperatures. Self-contained breathing apparatus (SCBA) is required if a large release occurs.

SECTION 7. HANDLING AND STORAGE

- Handling (Personnel) : Avoid breathing vapours or mist. Avoid contact with skin, eyes and clothing. Provide sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8.
- Handling (Physical Aspects) : The product should not be mixed with air for leak testing or used with air for any other purpose above atmospheric pressure. Contact with chlorine or other strong oxidizing agents should also be avoided.
- Dust explosion class : Not applicable
- Storage : Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems. Never attempt to lift cylinder by its cap. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.
Separate full containers from empty containers. Keep at temperature not exceeding 52°C. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present.
The product has an indefinite shelf life when stored properly.
- Storage period : > 10 yr
- Storage temperature : < 52 °C (< 126 °F)

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION


DuPont™ Suva® MP39 Refrigerant

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

- Engineering controls : Use sufficient ventilation to keep employee exposure below recommended limits. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places. Refrigerant Concentration monitors may be necessary to determine vapor concentrations in work areas prior to use of torches or other open flames, or if employees are entering enclosed areas.
- Personal protective equipment
- Respiratory protection : Under normal manufacturing conditions, no respiratory protection is required when using this product.
- Hand protection : Additional protection: Impervious gloves
- Eye protection : Wear safety glasses with side shields. Additionally wear a face shield where the possibility exists for face contact due to splashing, spraying or airborne contact with this material.
- Protective measures : Self-contained breathing apparatus (SCBA) is required if a large release occurs.

Exposure Guidelines
 Exposure Limit Values

Chlorodifluoromethane			
TLV	(ACGIH)	1,000 ppm	TWA
1-Chloro-1,2,2,2-tetrafluoroethane			
AEL *	(DUPONT)	1,000 ppm	8 & 12 hr. TWA
1,1-Difluoroethane			
AEL *	(DUPONT)	1,000 ppm	8 & 12 hr. TWA

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

**DuPont™ Suva® MP39 Refrigerant**

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

Physical state	: gaseous
Form	: Liquefied gas
Color	: colourless
Odor	: slight, ether-like
Odor threshold	: No applicable data available.
pH	: neutral
Melting point/range	: No applicable data available.
Boiling point/boiling range	: Boiling point -32.9 °C (-27.2 °F)
Flash point	: does not flash
Evaporation rate	: > 1 (CCL4=1.0)
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: Method: None per ASTM E681
Lower explosion limit	: Method: None per ASTM E681
Vapor pressure	: 7,765 hPa at 25 °C (77 °F)
Vapor density	: 3.3 at 25°C (77°F) and 1013 hPa (Air=1.0)
Specific gravity (Relative density)	: 1.19 at 25 °C (77 °F)
Water solubility	: 1.0 g/l at 25 °C (77 °F) at 1,013 hPa
Solubility(ies)	: No applicable data available.
Partition coefficient: n-octanol/water	: No applicable data available.
Auto-ignition temperature	: No applicable data available.
Ignition temperature	: 681 °C

**DuPont™ Suva® MP39 Refrigerant**

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

Decomposition temperature	:	No applicable data available.
Viscosity, kinematic	:	No applicable data available.
Viscosity	:	No applicable data available.
% Volatile	:	100 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable at normal ambient temperature and pressure.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Polymerization will not occur.
Conditions to avoid	:	Avoid open flames and high temperatures.
Incompatible materials	:	Alkali metals Alkaline earth metals, Powdered metals, Powdered metal salts
Hazardous decomposition products	:	Decomposition products are hazardous., This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrochloric and hydrofluoric acids, and possibly carbonyl halides., These materials are toxic and irritating., Avoid contact with decomposition products

SECTION 11. TOXICOLOGICAL INFORMATION

Chlorodifluoromethane (HCFC-22)		
Inhalation 4 h LC50	:	> 150000 ppm , Mouse
Inhalation Low Observed Adverse Effect Concentration (LOAEC)	:	50000 ppm , Dog Cardiac sensitization
Inhalation No Observed Adverse Effect Concentration	:	25000 ppm , Dog Cardiac sensitization
Skin irritation	:	Not expected to cause skin irritation based on expert review of the properties of the substance.
Eye irritation	:	Not expected to cause eye irritation based on expert review of the properties of the substance.


DuPont™ Suva® MP39 Refrigerant

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

- Skin sensitization : Not expected to cause sensitization based on expert review of the properties of the substance.
- Repeated dose toxicity : Inhalation
 Mouse
 -
 gas
 No toxicologically significant effects were found.
- Carcinogenicity : Not classifiable as a human carcinogen.
 Overall weight of evidence indicates that the substance is not carcinogenic.
- Mutagenicity : Animal testing did not show any mutagenic effects.
 Experiments showed mutagenic effects in cultured bacterial cells.
- Reproductive toxicity : No toxicity to reproduction
- Teratogenicity : Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity.
- Further information : Cardiac sensitisation threshold limit : 175000 mg/m3

1-Chloro-1,2,2,2-tetrafluoroethane (HCFC-124)

- Inhalation 4 h LC50 : > 230000 ppm , Rat
 Anaesthetic effects
 Central nervous system effects
- Inhalation Low Observed Adverse Effect Concentration (LOAEC) : 25000 ppm , Dog
 Cardiac sensitization
- Inhalation No Observed Adverse Effect Concentration : 10000 ppm , Dog
 Cardiac sensitization
- Skin irritation : Not expected to cause skin irritation based on expert review of the properties of the substance.
- Eye irritation : Not expected to cause eye irritation based on expert review of the properties of the substance.
- Skin sensitization : Not expected to cause sensitization based on expert review of the properties of the substance.
 Does not cause respiratory sensitisation.,


DuPont™ Suva® MP39 Refrigerant

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

There are no reports of human respiratory sensitization.

- Repeated dose toxicity : Inhalation
multiple species
-
No toxicologically significant effects were found.
- Carcinogenicity : Not classifiable as a human carcinogen.
- Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Animal testing did not show any mutagenic effects.
- Teratogenicity : Animal testing showed no developmental toxicity.
- Further information : Cardiac sensitisation threshold limit : 140000 mg/m3

1,1-Difluoroethane (HFC-152a)

- Inhalation 4 h LC50 : > 437500 ppm , Rat
- Inhalation No Observed Adverse Effect Concentration : 50000 ppm , Dog
Cardiac sensitization
- Inhalation Low Observed Adverse Effect Concentration (LOAEC) : 150000 ppm , Dog
Cardiac sensitization
- Skin sensitization : Does not cause respiratory sensitisation., Rat
- Repeated dose toxicity : Inhalation
Rat
-
NOAEL: 67.485 mg/l
No toxicologically significant effects were found.
- Carcinogenicity : Not classifiable as a human carcinogen.
Animal testing did not show any carcinogenic effects.
- Mutagenicity : Animal testing did not show any mutagenic effects.
Did not cause genetic damage in cultured bacterial cells.
Tests on mammalian cell cultures showed mutagenic effects.
- Reproductive toxicity : No toxicity to reproduction
Animal testing showed no reproductive toxicity.


DuPont™ Suva® MP39 Refrigerant

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

Teratogenicity : Animal testing showed no developmental toxicity.

Further information : Cardiac sensitisation threshold limit : 405000 mg/m3

Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ than those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

SECTION 12. ECOLOGICAL INFORMATION
Aquatic Toxicity
Chlorodifluoromethane (HCFC-22)

96 h LC50 : Zebra fish 777 mg/l

96 h EC50 : Algae 250 mg/l

48 h EC50 : Daphnia magna (Water flea) 433 mg/l

1,1-Difluoroethane (HFC-152a)

96 h LC50 : Fish 295.78 mg/l

96 h EC50 : Algae 47.76 mg/l

48 h EC50 : Daphnia (water flea) 146.7 mg/l

Environmental Fate
Chlorodifluoromethane (HCFC-22)

Biodegradability : According to the results of tests of biodegradability this product is not readily biodegradable.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal methods - : Can be used after re-conditioning. Recover by distillation or remove to a


DuPont™ Suva® MP39 Refrigerant

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

Product permitted waste disposal facility. Comply with applicable Federal, State/Provincial and Local Regulations.

Contaminated packaging : Empty pressure vessels should be returned to the supplier.

SECTION 14. TRANSPORT INFORMATION

DOT	UN number	: 3163
	Proper shipping name	: Liquefied gas, n.o.s. (Chlorodifluoromethane, 2-Chloro-1,1,1,2-Tetrafluoroethane)
	Class	: 2.2
	Labelling No.	: 2.2
IATA_C	UN number	: 3163
	Proper shipping name	: Liquefied gas, n.o.s. (Chlorodifluoromethane, 2-Chloro-1,1,1,2-Tetrafluoroethane)
	Class	: 2.2
	Labelling No.	: 2.2
IMDG	UN number	: 3163
	Proper shipping name	: LIQUEFIED GAS, N.O.S. (Chlorodifluoromethane, 2-Chloro-1,1,1,2-Tetrafluoroethane)
	Class	: 2.2
	Labelling No.	: 2.2

SECTION 15. REGULATORY INFORMATION

SARA 313 Regulated Chemical(s)	: 1-Chloro-1,2,2,2-tetrafluoroethane, Chlorodifluoromethane
PA Right to Know Regulated Chemical(s)	: Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): Chlorodifluoromethane
NJ Right to Know Regulated Chemical(s)	: Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): 1-Chloro-1,2,2,2-tetrafluoroethane,



DuPont™ Suva® MP39 Refrigerant

Version 2.0

Revision Date 03/13/2015

Ref. 130000050993

1,1-Difluoroethane, Chlorodifluoromethane

California Prop. 65 : Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known

SECTION 16. OTHER INFORMATION

Suva is a registered trademark of E. I. du Pont de Nemours and Company

® DuPont's registered trademark

Before use read DuPont's safety information.

For further information contact the local DuPont office or DuPont's nominated distributors.

Revision Date : 03/13/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.

