



Pressure Temperature Charts

°F	°C	R-514A
-40	-40	-14.2
-35	-37.2	-14.1
-30	-34.4	-14.0
-25	-31.7	-13.9
-20	-28.9	-13.7
-15	-26.1	-13.5
-10	-23.3	-13.3
-5	-20.6	-13.1
0	-17.8	-12.9
5	-15.0	-12.6
10	-12.2	-12.2
15	-9.4	-11.9
20	-6.7	-11.4
25	-3.9	-11.0
30	-1.1	-10.4
35	1.7	-9.9
40	4.4	-9.2
45	7.2	-8.5
50	10.0	-7.7
55	12.8	-6.9

°F	°C	R-514A
60	15.6	-5.9
65	18.3	-4.9
70	21.1	-3.8
75	23.9	-2.6
80	26.7	-1.2
85	29.4	0.2
90	32.2	1.8
95	35.0	3.5
100	37.8	5.3
105	40.6	7.3
110	43.3	9.4
115	46.1	11.7
120	48.9	14.1
125	51.7	16.7
130	54.4	19.5
135	57.2	22.4
140	60.0	25.6
145	62.8	29.0
150	65.6	32.5

Vapor Pressure in PSIG

Refrigerant Boiling Point

Refrigerant	Components	BP (0 PSIG):
R-514A	R-1336mzz(Z) (74.7%, Z-1,1,1,4,4,4-Hexafluoro-2-butene) R-1130(E) (25.3%, Trans-1,2-Dichloroethylene)	84.4°F

Liquid Density

Refrigerant	Liquid Density:	-80°F	-40°F	-0°F	40°F	80°F	120°F
R-514A	lb/cu. ft.	92.9	90.4	87.8	85.0	81.8	78.1
	lb/gal.	12.4	12.1	11.7	11.4	10.9	10.4

Physical Properties

	R-514A
Environmental Classification	HFO
Molecular Weight	139.6 g/mol
Boiling Point (1atm, °F)	84.4
Critical Pressure (psia)	510.5
Critical Temperature (°F)	352.5
Critical Density (lb./ft ^3)	25.68
Vapor Density (bp, lb./ft ^3)	0.37
Liquid Heat of Vaporization (bp, BTU/lb.)	100.1
Ozone Depletion Potential (CFC 11 -1.0)	0
Global Warming Potential (CO2 = 1.0)	2
ASHRAE Standard 34 Safety Rating	B1

Looking to Buy or Sell Refrigerant?

[See our Full Product Line](#)

Get **Paid** for Your Recovered
Refrigerant